



Addendum for R13 Models

IMPORTANT NOTICE PLEASE READ BEFORE YOU BEGIN SETUP

1. If you are setting up a cable box made by ARRIS, please use the codes listed on Page 20 of our Set-Up guide under Motorola first followed by General Instrument.
2. If you are setting up a cable box made by CISCO or TECHNICOLOR, please use the codes listed on Page 20 of our Set-Up guide under Scientific Atlanta.
3. NOTE that many newer cable and satellite boxes use Radio Frequency (RF) based remote control. The weemote only supports infrared (IR) remote control. Some of these systems allow you to enable IR signaling in their settings. You can tell if your system is using RF as your existing remote control can work without being pointed at the box, i.e. you could be turned completely around or even in a different room.
4. If your system uses sub-channels with more than one digit, for example channels like 10.12, 35.15, 23.40, etc then you will need to refer to the added instructions below as the current manual only addresses sub-channels with one digit like 10.3, 12.2, etc.

Refer to the example, Section C2 on Page 10 of the Set-Up Guide.

For example, to enter channel 10.35

Step 1: Press and Release the “10” button one time

Step 2: Press and release the B button to enter the sub-channel digits, i.e. 35.

Step 3: Press and Release the “10” button three times

Step 4: Press and Release the “1” button five times

Proceed to Section C3

